

Transparency class



Transparent



Semi-Transparent



Dim-Out

Applications



Curtains (Hand- / Cord- / Electrically operated Systems / Cubicle)



Wave Systems



Wave XL Systems



Roman Blind Systems



Sliding Panel Systems



Panel Fold Systems



Roller Blind Systems



Vertical Blind Systems



Vertical Wave Systems



Skylight Shading Systems



Dim-Out Blind Systems

Dimensions / Features / Technical properties



Fabric weight (g/m², DIN EN 12127)



Fabric thickness (mm, DIN ISO 2286-3)



Fabric width (cm)



Eco-tex Standard 100



Louvre width (mm)



Flame retardant



Colour fastness (DIN ISO 105-B02)



Applicable in humid areas

Washing instructions



Rub wet



Do not wash



Hand wash



30° C mild wash



Do not bleach



Do not tumble dry



Do not iron



Iron at low temperature



Iron at low temperature, no steam



Do not dry-clean



Dry-cleaning possible

Flame retardant (Standards)

B1 DIN 4102 (Deutsche Industrie Norm)

Type B / Type C BS 5867 (British Standards)

M1 / M2 NF P 92501-7 (Norme Française)

Class 1 CSE RF 1/75 (Ente Nazionale Italiano)